

# MAINE TIRE

## CHALLENGER 6400

Pneumatic Shaped Solids











### FEATURES

- Exceptional traction on loose/rough surface applications
- 250x15 and 300x15 feature 3 Stage construction and torque rings embedded in the base to resist wheel slippage in high torque applications
- 1000x20 and 1200x20 feature 2 Stage construction and are engineered to provide high performance
- Increased uptime while reducing maintenance costs and service calls
- Quick bolt on installation
- Available as an assembly - a new wheel with the Challenger 3 Stage (Easy Rider) tire
- Available in Non-Marking compound

### SPECS

R.D.	SIZE	RIM Wd.	NOTES	O.D.	S.W.	L.R.(lbs)		Wt.
						10mph	6mph	
15	250 - 15	7.00	HTR	28.1	8.9	6,960	9,615	162
15	250 - 15	7.50	HTR	28.4	9.3	7,460	10,300	164
15	300 - 15	8.00	HTR	32.4	11.4	9,550	13,190	257
20	1000 - 20	8.00	CS	39.5	9.4	10,010	13,825	306
20	1200 - 20	8.00	CS	41.8	10.1	13,475	18,605	365

### COMPOUNDS

 UNIVERSAL	 GLASS KING	 OIL RESISTANT
 POWER SAVER	 WIRE TEX	 TWR-TEAR WEAR RESISTANT
 ENDURANCE NON-MARKING	 GRIP SHELL	

### LEGEND

A - Skycap  
 B - Tarmax  
 C - Manlift  
 D - Airline  
 SFO - Special Factory Order  
 HTR - High Torque Rings in base of tire  
 CS - Compact Sizing