

MAINE TIRE

WOLVERINE

SMOOTH/TRACTION

Pneumatic Shaped Solids

FEATURES

- Full size global design that meets or exceeds TRA and ETRTO dimensional specifications
- Aggressive tread for extra traction incorporating proportional running bar
- Up to 75% greater tread depth for extended service
- Natural rubber formulated for high abrasion and tear resistance
- Scuff bar reduces side impact damage
- Center cushion compound absorbs shock resulting in greater driver comfort
- Concave sidewall flexes to reduce equipment damaging vibration
- Hysteresis properties of cushion compound results in reduced internal temperature in long run operations
- Compounded for low rolling resistance resulting in greater fuel savings and increased battery life
- Rim guard offers rim and wheel protection
- Base compounded and engineered for maximum strength and resistance to slipping on rims and wheels
- Available in Non-Marking compound

ASTM TEST

| | TREAD | CENTER | BASE |
|-------------------------|-----------|-----------|---|
| TENSILE STRENGTH P.S.I. | 3700 | 2800 | Base material is a quality engineered compound reinforced with high tensile nylon |
| 300% MODULUS P.S.I. | 2050 | 2000 | |
| ELONGATION% | 450 – 550 | 400 – 475 | |
| HARDNESS SHORE A | 65 | 62 | |
| BAYSHORE RESILIENCE% | 600 | 275 | |
| TEAR DIE.C P.L.I. | 47 | 52 | |

Smooth



Traction



MAINE TIRE

WOLVERINE

SMOOTH/TRACTION

Pneumatic Shaped Solids

SPECS

| SIZE | RIM Wd. | TREAD | O.D. | S.W. | L.R.(lbs) | | Wt. |
|-----------------|---------|-------|-------|------|-----------|--------|-------|
| | | | | | 10mph | 6mph | |
| 500 - 8 | 3.00 | DXT | 18.00 | 5.35 | 1,935 | 2,670 | 38.0 |
| 18 x 7 - 8 | 4.33 | DXT | 17.80 | 6.75 | 2,905 | 4,010 | 48.7 |
| 600 - 9 | 4.00 | DXT | 20.80 | 6.00 | 3,065 | 4,230 | 59.2 |
| 650 - 10 | 5.00 | DXT | 22.65 | 6.85 | 4,210 | 5,810 | 80.7 |
| 700 - 12 | 5.00 | DXT | 25.85 | 6.76 | 4,810 | 6,640 | 120.0 |
| 700 - 12 | 5.00 | S | 25.85 | 6.76 | 4,810 | 6,640 | 105.0 |
| 700 - 15 | 5.50 | DXT | 28.75 | 8.22 | 5,725 | 7,905 | 139.2 |
| 815/28 x 9 - 15 | 7.00 | DXT | 27.25 | 8.75 | 6,520 | 9,000 | 135.4 |
| 825 - 15 | 6.50 | DXT | 32.20 | 8.99 | 7,875 | 10,875 | 205.8 |

Smooth



Traction



3 STAGE CONSTRUCTION

