



MPR3 PNEUMATIC SHAPED SOLIDS

Multi-Purpose

SPECS

CODE	Size	Rim Wd.	O.D.	S.W.	Load Rating		Weight (lbs)
					6 mph	10 mph	
Traction							
913022	500-8	3.00	18.0	4.9	2,670	1,935	38.0
913034	18X7-8	4.33	18.0	5.6	4,695	3,400	41.0
913041	600-9	4.00	20.7	5.5	4,230	3,065	55.1
913051	650-10	5.00	22.8	6.2	5,810	4,210	76.1
913080	700-12	5.00	26.0	6.6	6,640	4,810	100.3
913122	700-15	5.50	28.8	7.0	7,905	5,725	120.2
913135	815-15	7.00	27.5	8.1	9,000	6,520	146.4
913139	825-15	6.50	32.2	8.0	10,875	7,875	193.3
913179	250-15	7.00	28.3	9.1	9,615	6,960	148.4
913180	300-15	8.00	32.2	10.0	13,190	9,550	218.5
913831	250-15	7.50	28.3	9.1	10,300	7,460	148.4
Traction Non-Marking							
914022	500-8	3.00	18.0	4.9	2,670	1,935	38.0
914034	18X7-8	4.33	18.0	5.6	4,695	3,400	41.0
914041	600-9	4.00	20.7	5.5	4,230	3,065	55.1
914051	650-10	5.00	22.8	6.2	5,810	4,210	76.1
914080	700-12	5.00	26.0	6.6	6,640	4,810	100.3
914122	700-15	5.50	28.8	7.0	7,905	5,725	129.2
914135	815-15	7.00	27.5	8.1	9,000	6,520	146.4
914139	825-15	6.50	32.2	8.0	10,875	7,875	198.2
914179	250-15	7.00	28.3	9.1	9,615	6,960	148.4
914180	300-15	8.00	32.2	10.0	13,190	9,550	225.5
914831	250-15	7.50	28.3	9.1	10,300	7,460	148.4

FEATURES

- 3-Stage, high quality, 100% natural rubber compound
- Soft riding center compound increases shock absorption
- Steel reinforced base maintains absolute fit
- Aggressive lug design for exceptional traction
- Steel reinforced base maintains absolute fit
- Dimensions meet all TRA standards
- Available in high performance Multi-Purpose and Non-Marking compounds



TRACTION



TRACTION NON-MARKING

